

UNITED STATES PATENT APPLICATION

FOR

MEASURING WHEEL BASE PARALLELISM WITH A
POSITION DETERMINATION SYSTEM

INVENTOR:

DAVID A. JACKSON
STEVEN GLICKMAN
HOSHANG SHROFF

FOSTER-12607860

MEASURING WHEEL BASE PARALLELISM WITH A POSITION DETERMINATION SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 60/199,366 filed
5 April 25, 2000 and U.S. Provisional Application No. 60/214,390, filed on June 28, 2000,
incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates generally to motor vehicle alignment and, more specifically,
to determining alignment of wheels relative to one another using a position determination
system.

BACKGROUND OF THE INVENTION

Motor vehicle alignment systems are important for ensuring that the alignments of wheels
on a vehicle are within the specifications provided by motor vehicle manufacturers. If the
wheels are out of alignment, there may be excessive or uneven wear. In addition, the
performance of the vehicle, particularly handling and stability, may be adversely affected if the
wheels are not properly aligned. As used herein, the term "wheel" or "vehicle wheel" refers to
the tire and wheel assembly found on a motor vehicle. Such an assembly generally includes a
conventional tire that is mounted on a metal wheel or "rim."

The wheels of a motor vehicle may be aligned in a number of ways. For example, an
20 operator or an alignment technician can use a vision imaging system such as a computer-aided,
three-dimensional (3D) machine vision that employs optical sensing devices, such as cameras, to
determine the positions of various objects. Although such machine vision systems are typically
used for alignment purposes, these systems can also be used to obtain other positional and

angular orientation information about a motor vehicle. Examples of such apparatus and methods are disclosed in U.S. Patent No. 5,724,743, entitled "Method and Apparatus for Determining the Alignment of Motor Vehicle Wheels," issued to Jackson, et al. on March 10, 1998 and in U.S. Patent No. 5,535,522, entitled "Method and Apparatus for Determining the Alignment of Motor Vehicle Wheels," issued to Jackson, et al. on July 16, 1996, each incorporated herein by reference. The apparatus disclosed in these patents is sometimes called a "3D aligner" or an "aligner," hereinafter referred to as a vision imaging system. As used herein, the term "position determination system" refers to an alignment system, such as the vision imaging system, in addition to other components used in conjunction with the alignment system to obtain positional and angular orientation information about a motor vehicle.

The above-described position determination system provides information, such as the centers of rotation of the vehicle's wheels, which aids in the wheel alignment of a vehicle. However, other information such as wheel parallelism, can also aid a technician in aligning the wheels of the vehicle. There is, therefore, a need for an improved method for using a position determination system capable of obtaining other positional information about a vehicle, such as wheel parallelism.

SUMMARY OF THE INVENTION

This and other needs are met by the present invention, which in accord with one aspect includes indicating wheel positions on the vehicle with targets; imaging the targets to obtain locations of the wheel positions; and calculating a relationship between the front and rear wheels. The calculation of the relationship between the front and rear wheels can include calculating a front wheel track extending between the two front wheels, calculating a rear wheel track

extending between the two rear wheels, and comparing an angle between the calculated front wheel track and the calculated rear track to a specified range for the angle. Furthermore, the calculated front and rear wheel tracks can be compared to specified ranges for the front and rear wheel tracks as an aid to a technician in aligning the wheels.

5 In another aspect, the calculation of the relationship between the front and rear wheels can include calculating a right wheel base with right wheel base being defined as the distance of a line passing adjacent to one of the right wheels and also perpendicularly from the wheel track passing through the wheel to the wheel track passing through the other of the right wheels. Furthermore, the calculation can include calculating a left wheel base with the left wheel base being defined as the distance of a line passing adjacent one of the left wheels and also perpendicularly from the wheel track passing through the wheel to the wheel track passing through the other of the left wheels. Alternatively, the right wheel base can be defined as between the two right wheels and the left wheel base can be defined as between the two left wheels. The calculated right and left wheel bases can be then compared to specified ranges for the right and left wheel bases as an aid to a technician in aligning the wheels.

10 In a further aspect, the calculation of the relationship between the front and rear wheels can include calculating a front center point of the front wheel track; calculating a rear center point of the rear wheel track; defining a line originating from the center point of one of the front and rear wheel tracks and perpendicular thereto and intersecting the other of the front and rear
20 wheel tracks; and calculating an offset distance from the intersection of the line with the other of the front and rear wheel tracks to the center point of the other of the front and wheel tracks. The calculated offset distance can then be compared to a specified range for offset distance as an aid to a technician in aligning the wheels.

In yet another aspect, the calculation of the relationship between the front and rear wheels can include calculating a first diagonal between the right, front wheel and the left, rear wheel; and calculating a second diagonal between left, front wheel and the right, rear wheel. After that, a difference between the first diagonal and the second diagonal can be calculated, and the calculated difference between the first diagonal and the second diagonal can be compared to a specified range for difference between the first diagonal and the second diagonal. Also, the calculated first diagonal can be compared to a specified range for the first diagonal, and the calculated second diagonal can be compared to a specified range for the second diagonal as an aid to a technician in aligning the wheels.

Additionally, a first skew angle can be calculated between the first diagonal and one of the wheel tracks; and a second skew angle can be calculated between the second diagonal and the one of the wheel tracks. After that, a difference between the first skew angle and the second skew angle can be calculated, and the calculated difference between the first skew angle and the second skew angle can be compared to a specified range for difference between the first skew angle and the second skew angle. Additionally, the calculated first skew angle can be compared to a specified range for the first skew angle, and the calculated second skew angle can be compared to a specified range for the second skew angle as an aid to a technician in aligning the wheels.

Additional advantages of the present invention will become readily apparent to those skilled in this art from the following detailed description, wherein only an exemplary embodiment of the present invention is shown and described, simply by way of illustration of the best mode contemplated for carrying out the present invention. As will be realized, the present invention is capable of other and different embodiments, and its several details are capable of

modifications in various obvious respects, all without departing from the invention. Accordingly, the drawings and description are to be regarded as illustrative in nature, and not as restrictive.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Reference is made to the attached drawings, wherein elements having the same reference numeral designations represent like elements throughout, and wherein:

 Figure 1 is a perspective view of a position determination system and a vision imaging system; and

 Figure 2 is a schematic view of the points obtained by the position determination system that are used to obtain a measure of parallelism of the wheel bases.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 A position determination system is capable of obtaining positional information about a vehicle, such as the parallelism of the wheels. Also, the offset and skew of the wheel base can be obtained. This is achieved, in part, by the position determination system determining the spatial relationship of one or more positions by using one or more cameras to image targets associated with each of the positions to be measured. The position determination system operates by imaging a target and comparing the imaged target to a base image of the target. Because the view path of the camera is known, it is possible to determine the angles at which the target is oriented to the view path and the exact location of the target in three-dimensional space. The
20 location of each position to be measured is then inferred from the location of the target associated with the position to be measured.

An example of a position determination system is illustrated in Fig. 1. The position determination system 100 includes a vision imaging system 102 having a pair of fixed, spaced-apart cameras 110, 112 mounted on a beam 114. The beam 114 has a length sufficient to position the cameras 110, 112 respectively outboard of the sides of the vehicle to be imaged by the position determination system 100. Also, the beam 114 positions the cameras 110, 112 high enough above the shop floor 116 to ensure that the two targets 118, 120 on the left side of the vehicle are both within the field of view of the left side camera 110, and two targets 122, 124 on the right side of the vehicle are both within the field of view of the right side camera 112.

INS
A1
FIG. 1
105
110
112
114
116
118
120
122
124
126
128
130
132
134
136
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

Targets 118, 120, 122, 124 are mounted on each of the wheels 126, 128, 130, 132 of the motor vehicle, with each target 118, 120, 120, 124 including a target body 134, target elements 136, and an attachment apparatus 138. The attachment apparatus 138 attaches the target 118, 120, 120, 124 to wheel 126, 128, 130, 132. An example of an attachment apparatus is described in U.S. Patent No. 5,024,001, entitled "Wheel Alignment Rim Clamp Claw" issued to Borner et al. on June 18, 1991, incorporated herein by reference. The target elements 136 are positioned on the target body 134. Examples of target bodies 134 and target elements 112 acceptable for use in the invention are described in U.S. Patent No. 5,724,743.

INS
A2
FIG. 2
105
110
112
114
116
118
120
122
124
126
128
130
132
134
136
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

In operation, once the position determination system 100 has been calibrated using a calibration target (not shown), as described in the incorporated references, a vehicle can be driven onto the rack 133, and, if desired, the vehicle lifted to an appropriate repair elevation.

20 The targets 118, 120, 122, 124, once attached to the wheel rims, are then oriented so that the target elements 136 on the target body 134 face the respective camera 110, 112. The vehicle and model year can then entered into the vision imaging system 102 along with other identifying parameters, such as vehicle VIN number, license number, owner name, etc.

The location of the targets 118, 120, 122, 124 relative to the rim of the wheels 126, 128, 130, 132 to which the targets are attached are typically known to an accuracy of about 0.01" and about 0.01°. Once the targets 118, 120, 122, 124 have been imaged in one position, the wheels 126, 128, 130, 132 are rolled to another position and a new image can be taken. Using the imaged location of the targets 118, 120, 122, 124 in the two positions, the actual position and orientation of the wheels 126, 128, 130, 132 and wheel axis can be calculated by the vision imaging system 102. Although the distance between the two positions varies, the distance is often approximately 8 inches.

Fig. 2 schematically illustrates information obtained about the wheels 126, 128, 130, 132, wheel track 150, 152, and wheel base 154, 156. As calculated by the position determination system 100, the front wheel track 150 extends between the two wheel positions P_1 , P_3 used to define the locations of the two front wheels 126, 130 and has a center point 150a. Also, the rear wheel track 152 extends between the two wheel positions P_2 , P_4 used to define the locations of the two rear wheels 128, 132 and has a center point 152a. The locations of the wheel positions P_1 , P_2 , P_3 , P_4 are obtained from the position determination system 100 imaging the targets 118, 120, 122, 124 disposed on the wheels 126, 128, 130, 132. The right wheel base 154 is calculated as the distance between the two wheel positions P_3 , P_4 used to define the locations of the two right wheels 126, 128. The left wheel base 156 is calculated as the distance between the two wheel positions P_1 , P_2 used to define the positions of the two left wheels 130, 132. It should be noted that the wheel positions P_1 , P_2 , P_3 , P_4 to define the positions of the wheels 126, 128, 130, 132 can be any common location along the axis of rotation of the wheels 126, 128, 130, 132. Also, the wheel base 154, 156 can be the perpendicular distance between the front wheels 126, 130 and the rear wheels 128, 132, as illustrated, or the wheel base 154, 156 can be the straight

line distance between the wheel positions P_1 , P_3 used to define the locations of the front wheels 126, 130 and the wheel positions P_2 , P_4 used to define the positions of the rear wheels 128, 132.

Once calculated, the wheel track 150, 152 and wheel base 154, 156 can be compared, for example manually or by the position determination system, to a desired range for wheel track and wheel base for the particular vehicle being inspected. This comparison of the calculated wheel track 150, 152 and wheel base 154, 156 to a desired range can then be used by the technician as an aid in the alignment of the vehicle.

Another aid to the technician is to have the position determination system 100 compare the wheel tracks 150, 152 to each other with regard to parallelism and display the angular difference. The wheel tracks 150, 152 are perfectly parallel if the imaginary lines defined by the wheel tracks 150, 152 are 0° apart. The position determination system 100 can also display a desired range of the angle between the wheel tracks 150, 152, for example 0.00 to 0.50° , and indicate to the technician with the calculated angle is within the desired range.

INS
A3
The information obtained about the wheels 126, 128, 130, 132 can also include a measure of skew. When the plane defined by the wheels 126, 128, 130, 132 is a trapezoid or parallelogram instead of a square, skew is a measure of the difference between the trapezoid or parallelogram with the square. For example, diagonal lines 158, 160 can be respectively drawn between the left, front wheel 126 and the right, rear wheel 132 and between the right, front wheel 130 and the left, rear wheel 128. One measure of skew is the difference between the length of these diagonal lines 158, 160. If, for example, diagonal line 158 is longer than diagonal line 160, the rear wheels 128, 130 are skewed to the right. Conversely, if diagonal line 158 is shorter than diagonal line 160, the rear wheels 128, 130 are skewed to the left. The position determination system 100 can display the length of the diagonal lines 158, 160 and can also compare the

diagonal lines 158 to each other. Additionally, the position determination system can compare the length of the diagonal lines to a desired range of lengths for the particular vehicle being measured.

IVS
A4 5

Another measure of skew is to compare the skew angles 162a, 162b between the wheel tracks 150, 152 and the diagonal line 158 from the left, front wheel 126 to the right, rear wheel 132 and the skew angles 164a, 164b between the wheel tracks 150, 152 and the diagonal line 160 from the right, front wheel 130 to the left, rear wheel 128. If, for example, skew angles 162a, 162b are smaller than skew angles 164a, 164b, this indicates that the rear wheels 128, 130 are skewed to the right. Conversely, if skew angles 162a, 162b are larger than skew angles 164a, 164b, the rear wheels 128, 130 are skewed to the left. The position determination system 100 can display the skew angles 162a, 162b, 164a, 164b and can also compare skew the angles 162a, 162b, 164a, 164b to one another. Additionally, the position determination system can compare the skew angles 162a, 162b, 164a, 164b to a desired range of skew angles for the particular vehicle being measured.

FO5570-72607600

A measure similar to skew is offset, which is defined as the distance from the center point 152a, 150a of the wheel track 152, 150 to an intersection point 166 of a line 168 with the wheel track 152, 150. The line 168 originates from the center point 150a, 152a of the other wheel track 150, 152 and is perpendicular to the other wheel track 150, 152. Two offset values can be obtained depending upon from which wheel track 150, 152 the line 168 originates perpendicularly. Also, depending upon the orientation of the wheel tracks 150, 152, the two offset values can be different from each other. If, however, the wheel tracks 150, 152 are parallel, the two offset values will be identical. In this manner, a comparison of the two offset values with each other can be used to determine whether the wheel tracks 150, 152 are parallel.

The position determination system 100 can display one or both of the offset values and can compare the these offsets to each other. Additionally, the position determination system can compare one or both of the offsets to a desired range of offsets for the particular vehicle being measured.

5 The present invention can be practiced by employing conventional materials, methodology and equipment. Accordingly, the details of such materials, equipment and methodology are not set forth herein in detail. In the previous descriptions, numerous specific details are set forth, such as specific materials, structures, chemicals, processes, etc., in order to provide a thorough understanding of the present invention. However, it should be recognized that the present invention can be practiced without resorting to the details specifically set forth. In other instances, well known processing structures have not been described in detail, in order not to unnecessarily obscure the present invention.

Only an exemplary aspect of the present invention and but a few examples of its versatility are shown and described in the present disclosure. It is to be understood that the present invention is capable of use in various other combinations and environments and is capable of changes or modifications within the scope of the inventive concept as expressed herein.